

## ADVANTAGES

- Special for drill countersinking reamers and taper-lok cutters:
- - RB 356 HPI 58 for use with taper-lok cutters
- - RB 356 HP 58 for use with cutters RB 022

## PRECISION MANUFACTURING

- Detachable spindle adapter provides alternative methods for use:
  - In combination with 3 jaw chuck.
  - Mounting direct onto machine spindle. This method provides increased level of concentricity, while reducing the length and weight of the drill / tool assembly. This results in better performance, improved machining, and less fatigue on the operator.
- Cemented, hardened, and ground chrome-nickel steel spindle mounted on 3 needle-bearings and a thrust bearing.
- Microstop depth adjustment (1 scale division = 0.001 in).
- Microstop depth setting is held securely in place by locknut with seal. This patented feature allows an easy loosening of the locknut without damage to the drill cage.



Basic Drill Cage + Adapter  
RB 356 HP 58 / RB 356 HPI 58



Mounting Base Flat Bearing  
90815140W



Mounting Base Flat Bearing  
90815140

(Pictures are for illustration purposes only)

RB 356 HP 58		MICROSTOP CAGE ASSEMBLY CODE*	
		1005000W	10050000
RB 356 HPI 58		10050050W	10050050
Basic Drill Cage + Adapter		●	●
Mounting Base Large Window	90815140W	●	
Mounting Base Flat Bearing	90815140		●

\*Add CJ or CJW to the reference for Jacobs cone adapter.

MICROSTOP CAGE												
	T		D1	D2	H1		H2		Stroke	D3	L3	D4
<b>RB 356 HP 58</b>	M10 x 1	mm	10	36	Min	Max	Min	Max	58	30	103	38
<b>RB 356 HPI 58</b>	7/16 in - 20	in	0.39	1.42	2.52	3.62	10.39	11.50	2.28	1.18	4.06	1.50

